


| IPS      |     |          |
|----------|-----|----------|
| SIZE     | A   | <u>B</u> |
| 2"<br>3" | 4.5 | 4.88     |
| 3"       | 4.5 | 5        |
| 4"       | 6   | 6.63     |
| 6"       | 7   | 7.88     |
| 8"       | 7.5 | 8.63     |
| 10"      | 7.5 | 9        |
| 12"      | 9   | 10.75    |
| 14"      | 9   | 10.88    |
| 16"      | 9   | 11.13    |
| 18"      | 10  | 12.38    |
| 20"      | 10  | 12.63    |
| 22"      | 12  | 15       |
| 24"      | 12  | 15.25    |
| 26"      | 14  | 17.5     |
| 28"      | 16  | 19.75    |
| 30"      | 16  | 20       |
| 32"      | 16  | 20.25    |
| 34"      | 16  | 20.5     |
| 36"      | 20  | 24.88    |
| 42"      | 20  | 25.63    |
| 48"      | 20  | 26.5     |
| 54"      | 20  | 27.25    |
| 63"      | 20  | 28.5     |

HDPE FABRICATED 30-deg ELBOWS PLAIN-END/BUTT-FUSE DR9-32.5 FULLY RATED DR7 DE-RATED PE4710

> DATE 8-10-18



Fittings between 20" and 48" are designed to be fused on a 1648 or smaller field machine, If longer lengths are required, please contact Sandale Utility Products for special requirements.

## **DISCLAIMER - PLEASE READ**

- 1) All dimensions approximate, subject to change without notice
  - -- Angle tolerance is +/- 2 degrees
  - --All other dimensions to +/- 1"
- 2) This drawing only applicable if a copy is referenced at time of order.
  - --Without a copy of drawing, fitting construction may differ from that shown.
- 3) Subject to manufacturer's terms and conditions.